

EC Centrifugal Fans

Product overview




EC Centrifugal Fans 250–280 mm

Hidria EC centrifugal fans with backward curved blades designed for various applications.

EC motor family	R10	R10	R14	R14
Diameter range	250 mm	280 mm	280 mm	280 mm
Nominal voltage	230 V	230 V	230 V	400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Power input range	270 W	350 W	800 W	1.400 W
Max. air volume (free air flow)	2.300 m ³ /h	2.900 m ³ /h	3.700 m ³ /h	4.600 m ³ /h
Protection class	IP54	IP54	IP54	IP54
Insulation class	B	B	B	F
Min. amb. temperature	-25 °C	-25 °C	-25 °C	-25 °C
Max. amb. temperature	+65 °C	+55 °C	+60 °C	+60 °C
Speed control options	0-10V, 4-20 mA, PWM, MODBUS RTU			

AD specifications



Integrated connectivity and control – Motion concept

NFC and Bluetooth connectivity built-in for wireless connectivity, with preventive maintenance readiness. User friendly inverter unit allows for easy (single tool) mounting/dismounting of the complete inverter unit.




EC Centrifugal Fans

315–400 mm

Hidria EC centrifugal fans offer maximum operational reliability and performance, low operating costs and low environmental pollution through continuous speed control.

EC motor family	R14	R14	R14	R14
Diameter range	315 mm	315 mm	355 mm	400 mm
Nominal voltage	230 V	400 V	400 V	400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Power input range	900 W	1.500 W	1.500 W	1.500 W
Max. air volume (free air flow)	4.600 m ³ /h	5.400 m ³ /h	6.500 m ³ /h	7.700 m ³ /h
Protection class	IP54	IP54	IP54	IP54
Insulation class	B	F	F	F
Min. amb. temperature	-25 °C	-25 °C	-25 °C	-25 °C
Max. amb. temperature	+50 °C	+55 °C	+60 °C	+60 °C
Speed control options	0-10V, 4-20 mA, PWM, MODBUS RTU			

AD specifications



EC motor with integrated electronics

Industry latest speed control options and highly efficient performance of the synchronized motor-electronics combination. Testing of EC fans after production and traceability of each electronic during complete process.




EC Centrifugal Fans

450–560 mm

All production processes for the electronics as well as its programming, testing and installation, are performed in a clean room in which the ESD safety standards are observed.

EC motor family	R14	R18	R18	R18
Diameter range	450 mm	450 mm	500 mm	560 mm
Nominal voltage	400 V	400 V	400 V	400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Power input range	1.500 W	3.200 W	3.300 W	3.400 W
Max. air volume (free air flow)	9.100 m ³ /h	11.700 m ³ /h	13.100 m ³ /h	15.300 m ³ /h
Protection class	IP54	IP55	IP55	IP55
Insulation class	F	F	F	F
Min. amb. temperature	-25 °C	-25 °C	-25 °C	-25 °C
Max. amb. temperature	+55 °C	+60 °C	+60 °C	+60 °C
Speed control options	0-10V, 4-20 mA, PWM, MODBUS RTU			

AD specifications



Innovative design – patented motor cooling

Besides other innovative solutions implemented to our fans one of the most advanced is patented motor cooling which assure lower temperature at the electronic zone. This consequently increase reliability and life time of the fans.





Hidria

quality and innovation assurance

Through more than **50 years of tradition**, the company Hidria has become an established provider of innovative energy-efficient AC and EC electrical motors and fans for heating, ventilation, air-conditioning, refrigeration and other applications.

As a development supplier, we pay special attention to several factors that play an important role in the production and development of our products. Our solutions are supported by our own R&D staff, laboratories and production facilities, which contribute to the quality of the final product.

Through the development process, we test our fans under different conditions in order to achieve their maximum performance and quality. Field tests are also an important part of this process, during which we run our fans in a test area where they are exposed to harsh environmental influences through the whole year. This way our fans are tested under real environmental conditions.



Sales and distribution:

AUSTRALIA AND NEW ZEALAND

BEIJER REF AUSTRALIA
10/88 Dynon Road
3003 West Melbourne
VIC Australia
T: +613 9371 1300
F: +613 9372 5580
E: info@beijerref.com.au

MIDDLE EAST

NASER AL SAYER & CO. L.L.C.
P.O. Box 1825
Al Maktoum Hospital Road,
Deira, Dubai, U.A.E.
T: 00971-4-2222-471
E: nascomt@emirates.net.ae
www.nasco-uae.com/
refrigeration

ZILAL COOLING & TRADING
EST. P.O. Box 27959 - 11427
Al Ihsa Street,
Riyadh, Saudi Arabia
T: 00966-11-4790340
E: abd@zilalcooling.com
www.zilalcooling.com

EBRAHIM AL-JASSIM SONS
TRADING CO., LTD.
PO Box.102, King Kaled St.
DAMMAM-31411, Saudi Arabia
T: +966 13 8332109 Extn. 111
E: mejassim@al-jassim.com

CHINA

Zhejiang RUIXUE Refrigeration
Equipment Technology Co., Ltd.
No.188 Jiaocang Road,
Ganlin Industrial Zone
Shengzhou City, Zhejiang
Province, China
T: +86 21 54198596
M: +86 173 1715 4744
F: +86 21 5419 8522
E: tiffany.s@shemth.com
www.shemth.com

SOUTH KOREA

DAESUNG MAREF CO., LTD
851-8, Hwasan-ri Ujeong-eup
Hwaseong city Gyeonggi-do,
Korea
T: +82 31 421 8883
E: dsc@dsmaref.com

SOUTHEAST ASIA

Dixell (Asia) Co., Ltd.
2893, 2895 Phattanakan Road
Suanluang 10250,
Bangkok, Thailand
T: +66 2 722 0245-9
F: +66 2 320 2520
E: dixell@dixellasia.com
www.dixellasia.com

BELGIUM

Refritec bvba/sprl
Weiveldlaan 7
1930 Zaventem
T: +32 (0)2 715 24 44
F: +32 (0)2 715 24 46
E: info@refritec.be
www.refritec.be

NEDERLAND

BEIJER REF SUPPORT BV
Westfields 1210
5688 HA Oirschot Nederland
www.beijerref.nl
T: +31 180 751 300
F: +31 180 751 305

SERBIA

FRIGO RADAK COMPANY D.O.O.
Đurđevdanska 20
11000 Beograd, Serbia
T: +381 11 3945577
M: +381 63 318539
E: bobanradak@yahoo.com
www.frigoradak.com

SLOVENIA

EMPOR d.o.o.
Leskoškova 9a,
1000 Ljubljana
T: +386 1 5203820
E: empor@empor.si
www.empor.si

SPAIN

Refrigeration & Climate
Control, S.L.U.
Calle 2A, 7 ; Pol. Ind. Tactica
46980 Paterna (Valencia),
Spain
T: 0034-96-159-49-33
E: direccion@r-cc.es
www.r-cc.es

SWEDEN AND DENMARK

ARMATEC AB
Betagatan 1,
431 49 Mölndal, Sweden
T: +46 31890100
E: info@armatec.se
www.armatec.se



Hidria d. o. o.

Spodnja Kanomlja 23
5281 Spodnja Idrija
Slovenia
T: +386 5 375 60 00
E: sales.fans@hidria.com
www.hidria.com



FAN SELECTION

Scan QR code or visit:
fanselection.hidria.com

