



Hidria
Gonvarri Industries

EC Centrifugal Fans

PRODUCT OVERVIEW




EC Centrifugal Fans 250–280 mm

Hidria EC centrifugal fans with backward curved blades designed for various applications.

EC motor family	R10	R10	R14	R14
Diameter range	250 mm	280 mm	280 mm	280 mm
Nominal voltage	230 V	230 V	230 V	400 V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Power input range	270 W	350 W	800 W	1400 W
Max. air volume (free air flow)	2.300 m³/h	2.900 m³/h	3.700 m³/h	4.600 m³/h
Protection class	IP54	IP54	IP54	IP54
Insulation class	B	B	B	F
Min. amb. temperature	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)
Max. amb. temperature	65 °C / 149 °F	55 °C / 131 °F	60 °C / 140 °F	60 °C / 140 °F
Speed control options	0-10, 4-20 mA, PWM, MODBUS RTU			

AD specifications



Integrated connectivity and control – Motion concept

Using the free Hidria Fan App, available for iOS and Android mobile devices, and NFC connection to the fan, the user can freely set key parameters of the fan and monitor its operation. Based on the collected data, we can easily perform an analysis of the operation and predict the remaining life of the fan. The full functionality of the Fan App is achieved with the option of fan refurbishment, as using the Hidria Fan App it is possible to easily transfer the parameter settings of the worn-out electronics to the newly installed EC fan electronics.




EC Centrifugal Fans 310–400 mm

Hidria EC centrifugal fans offer maximum operational reliability and performance, low operating costs and low environmental pollution through continuous speed control.


EC motor family	R14	R14	R14	R14
Diameter range	310 mm	310 mm	355 mm	400 mm
Nominal voltage	230 V	400 V	400 V	400 V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Power input range	900 W	1.500 W	1.500 W	1.500 W
Max. air volume (free air flow)	4.600 m ³ /h	5.400 m ³ /h	6.500 m ³ /h	7.700 m ³ /h
Protection class	IP54	IP54	IP54	IP54
Insulation class	B	F	F	F
Min. amb. temperature	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)
Max. amb. temperature	50 °C / 122 °F	55 °C / 131 °F	60 °C / 140 °F	60 °C / 140 °F
Speed control options	0-10, 4-20 mA, PWM, MODBUS RTU			

AD specifications



EC motor with integrated electronics

Industry latest speed control options and highly efficient performance of the synchronized motor-electronics combination. Testing of EC fans after production and traceability of each electronic during complete process.




EC Centrifugal Fans R14S

310–450 mm

Additional R14 Supreme range is developed to reach higher performance and aerodynamic characteristic of R14 motor range with optimized and competitive price of fan. Very suitable for compact and modular AHU, data cooling centers AHU, ventilation boxes and other HVAC applications.

EC motor family	R14 S	R14 S	R14 S	R14 S
Diameter range	310 mm	355 mm	400 mm	450 mm
Nominal voltage	400 V	400 V	400 V	400 V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Power input range	2.600 W	3.000 W	3.000 W	2.600 W
Max. air volume (free air flow)	6.300 m³/h	8.200 m³/h	9.700 m³/h	10.600 m³/h
Protection class	IP55	IP55	IP55	IP55
Insulation class	B	F	F	F
Min. amb. temperature	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)
Max. amb. temperature	40 °C / 104 °F	40 °C / 104 °F	40 °C / 104 °F	40 °C / 104 °F
Speed control options	0-10, 4-20 mA, PWM, MODBUS RTU			

AD specifications



Integrated powerful electronic control R18

Fan wall solution allows use in extreme high AD applications demand, supported with a lot of different versions available, with or without plate and brackets. Version for higher ambient temperature application with additional motor cooling solution is available.




EC Centrifugal Fans 450–630 mm

All production processes for the electronics as well as its programming, testing and installation, are performed in a clean room in which the ESD safety standards are observed.


EC motor family	R18	R18	R18	R18
Diameter range	450 mm	500 mm	560 mm	630 mm
Nominal voltage	400 V	400 V	400 V	400 V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Power input range	3.200 W	3.300 W	3.400 W	3.200 W
Max. air volume (free air flow)	11.700 m³/h	13.100 m³/h	15.300 m³/h	17.400 m³/h
Protection class	IP55	IP55	IP55	IP55
Insulation class	F	F	F	F
Min. amb. temperature	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)	-25 °C (-13 °F)
Max. amb. temperature	60 °C / 140 °F	60 °C / 140 °F	60 °C / 140 °F	50 °C / 122 °F
Speed control options	0-10, 4-20 mA, PWM, MODBUS RTU			

AD specifications



Innovative design – patented motor cooling

Besides other innovative solutions implemented to our fans one of the most advanced is patented motor cooling which assure lower temperature at the electronic zone. This consequently increase reliability and life time of the fans.



Sales and distribution:

NORTH AMERICA & MEXICO

Servitek Solutions
2001 Timberloch Place,
Suite 500
The Woodlands, Texas 77380
T: +1 713-588 43 46
E: salvador.vazquez@hidria.com

SOUTHEAST ASIA

Dixell (Asia) Co., Ltd.
2893, 2895 Phattanak Road
Suanluang 10250,
Bangkok, Thailand
T: +66 2 722 0245-9
F: +66 2 320 2520
E: dixell@dixellasia.com
www.dixellasia.com

AUSTRALIA AND NEW ZEALAND

BEIJER REF AUSTRALIA
10/88 Dynon Road
3003 West Melbourne
VIC Australia
T: +613 9371 1300
F: +613 9372 5580
E: info@beijerref.com.au

MIDDLE EAST

NASER AL SAYER & CO. L.L.C.
P.O. Box 1825
Al Maktoum Hospital Road,
Deira, Dubai, U.A.E.
T: 00971-4-2222-471
E: nascomt@emirates.net.ae
www.nasco-uae.com/
refrigeration

ZILAL COOLING & TRADING
EST. P.O. Box 27959 - 11427
Al Ihsa Street,
Riyadh, Saudi Arabia
T: 00966-11-4790340
E: abd@zilalcooling.com
www.zilalcooling.com

EBRAHIM AL-JASSIM SONS
TRADING CO., LTD.
PO Box.102, King Kaled St.
DAMMAM-31411, Saudi Arabia
T: +966 13 8332109 Extn. 111
E: mejassim@al-jassim.com

BELGIUM

Refritec bvba/sprl
Weiveldlaan 7
1930 Zaventem
T: +32 (0)2 715 24 44
F: +32 (0)2 715 24 46
E: info@refritec.be
www.refritec.be

NEDERLAND

BEIJER REF SUPPORT BV
Westfields 1210
5688 HA Oirschot Nederland
www.beijerref.nl
T: +31 180 751 300
F: +31 180 751 305

SERBIA

FRIGO RADAK COMPANY D.O.O.
Đurđevdanska 20
11000 Beograd, Serbia
T: +381 11 3945577
M: +381 63 318539
E: bobanradak@yahoo.com
www.frigoradak.com

SLOVENIA

EMPOR d.o.o.
Leskoškova 9a,
1000 Ljubljana
T: +386 1 5203820
E: empor@empor.si
www.empor.si

SPAIN

Refrigeration & Climate
Control, S.L.U.
Calle 2A, 7 ; Pol. Ind. Tactica
46980 Paterna (Valencia),
Spain
T: 0034-96-159-49-33
E: direccion@r-cc.es
www.r-cc.es

SWEDEN AND DENMARK

ARMATEC AB
Betagatan 1,
431 49 Mölndal, Sweden
T: +46 31890100
E: info@armatec.se
www.armatec.se



UL/CSA Recognized
component:

FAN SELECTION

Scan QR code or visit:
fanselection.hidria.com



Hidria d. o. o. | Spodnja Kanomlja 23, 5281 Spodnja Idrija, Slovenia
T: +386 5 375 60 00 | E: sales.fans@hidria.com | www.hidria.com

