


EC Centrifugal Fans

Product overview



A detailed view of a mechanical component, possibly a motor or pump, with a blue overlay containing text. The component is metallic and features three circular ports on top. The blue overlay is semi-transparent and contains white text.

Unique components for efficient and optimized performance

Carefully selected and designed components that enable the most optimal performance.

EC Centrifugal Fans

280–315 mm

Hidria EC centrifugal fans with backward curved blades designed for various applications.

EC motor family	R10	R14	R14
Diameter	280 mm	280 mm	315 mm
Nominal voltage	230 V	400 V	400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Power input	350 W	1.000 W	1.000 W
Max. air volume (free air flow)	3.000 m ³ /h	4.200 m ³ /h	4.900 m ³ /h
Protection class	IP54	IP54	IP54
Insulation class	B	B	B
Min. amb. temperature	-35 °C	-35 °C	-35 °C
Max. amb. temperature	+40 °C	+40 °C	+40 °C
Speed control options	0-10V, 4-20 mA, PWM, MODBUS RTU	0-10V, 4-20 mA, PWM, MODBUS RTU	0-10V, 4-20 mA, PWM, MODBUS RTU

■ Compact design

Safe, simple and compact design that enables easy installation and optimal performance of the entire assembly. Compact design does not only enable its balanced performance, but also saves space compared to conventional inverter driven fans.



■ EC motor with integrated electronics

Industry latest speed control options and highly efficient performance of the synchronized motor-electronics combination.



■ Carefully selected components

External rotor motor design allows high efficiency impeller to be installed directly on the rotor. In addition, the entire motor-impeller assembly is supported with the corrosion resistant support brackets and inlet nozzle that offers the most optimal intake and distribution of the air-flow.




EC Centrifugal Fans

350–450 mm

Hidria EC centrifugal fans offer maximum operational reliability and performance, low operating costs and low environmental pollution through continuous speed control.

EC motor family	R14	R14	R14
Diameter	350 mm	400 mm	450 mm
Nominal voltage	400 V	400 V	400 V
Frequency	50/60 Hz	50/60 Hz	50/60 Hz
Power input	1.000 W	1.000 W	1.000 W
Max. air volume (free air flow)	5.600 m ³ /h	6.400 m ³ /h	7.800 m ³ /h
Protection class	IP54	IP54	IP54
Insulation class	B	B	B
Min. amb. temperature	-35 °C	-35 °C	-35 °C
Max. amb. temperature	+40 °C	+40 °C	+40 °C
Speed control options	0-10V, 4-20 mA, PWM, MODBUS RTU	0-10V, 4-20 mA, PWM, MODBUS RTU	0-10V, 4-20 mA, PWM, MODBUS RTU

AD specifications




Hidria

quality and innovation assurance

Through more than **45 years of tradition**, the company Hidria Rotomatika has established its process of innovation and quality assurance. With the help of a highly sophisticated and equipped R&D team, we are able to deliver solutions that achieve the most optimal performance for their applications.

As a development supplier, we pay special attention to several factors that play an important role in the production and development of our products. Our solutions are supported by our own R&D staff, laboratories and production facilities, which contribute to the quality of the final product.

Through the development process, we test our fans under different conditions in order to achieve their maximum performance and quality. Field tests are also an important part of this process, during which we run our fans in a test area where they are exposed to harsh environmental influences through the whole year. This way our fans are tested under real environmental conditions.



Sales and distribution:

AUSTRALIA AND NEW ZEALAND

BEIJER REF AUSTRALIA
10/88 Dynon Road
3003 West Melbourne
VIC Australia
T: +613 9371 1300
F: +613 9372 5580
E: info@beijerref.com.au

MIDDLE EAST

NASER AL SAYER & CO. L.L.C.
P.O. Box 1825
Al Maktoum Hospital Road,
Deira, Dubai, U.A.E.
T: 00971-4-2222-471
E: nascomt@emirates.net.ae
www.nasco-uae.com/
refrigeration

ZILAL COOLING & TRADING EST.

P.O. Box 27959 - 11427
Al Ihsa Street, Riyadh,
Saudi Arabia
T: 00966-11-4790340
E: abd@zilalcooling.com
www.zilalcooling.com

EBRAHIM AL-JASSIM SONS TRADING CO., LTD.

PO Box.102, King Kaled St.
DAMMAM-31411, Saudi Arabia
T: +966 13 8332109 Extn. 111
E: mejassim@al-jassim.com

CHINA

Zhejiang RUIXUE Refrigeration
Equipment Technology Co., Ltd.
No.188 Jiaocang Road,
Ganlin Industrial Zone
Shengzhou City,
Zhejiang Province, China
T: +86 21 54198596
M: +86 173 1715 4744
F: +86 21 5419 8522
E: tiffany.s@shemth.com
www.shemth.com

SOUTH KOREA

DAESUNG MAREF CO., LTD
851-8, Hwasan-ri Ujeong-eup
Hwaseong city Gyeonggi-do,
Korea
T: +82 31 421 8883
E: dsc@dsmaref.com

SOUTHEAST ASIA

Dixell (Asia) Co., Ltd.
2893, 2895 Phattanakan Road
Suanluang 10250,
Bangkok, Thailand
T: +66 2 722 0245-9
F: +66 2 320 2520
E: dixell@dixellasia.com
www.dixellasia.com

BELGIUM

Refritec bvba/sprl
Weiveldlaan 7
1930 Zaventem
T: +32 (0)2 715 24 44
F: +32 (0)2 715 24 46
E: info@refritec.be
www.refritec.be

BULGARIA

NOVOTECHPROM OOD
6000 Stara Zagora
Kv. Industrialen
Kaloianovsko shose str., 16
Bulgaria
T: +359 42 603 309
E: ntp@novotechprom.com
www.novotechprom.com

FINLAND AND ESTONIA

REPAIR OY
Atomitie 1 FIN-00370
Helsinki, Finland
T: +358 9 5657780
E: info@refair.fi
www.refair.fi

NEDERLAND

BEIJER REF SUPPORT BV
Westfields 1210
5688 HA Oirschot
Nederland
www.beijerref.nl
T: +31 180 751 300
F: +31 180 751 305

RUSSIA

PHS LLC
Savvinskoye shosse 10, floor 6.
Zheleznodorozhniy mkr.
Balashikha,
Moscow region, Russia
T: +7-495-221-22-79
E: ak@phs-holod.ru
www.phs-holod.ru

SERBIA

FRIGO RADAK COMPANY D.O.O.
Đurđevdanska 20
11000 Beograd, Serbia
T: +381 11 3945577
M: +381 63 318539
E: bobanradak@yahoo.com
www.frigoradak.com

SLOVENIA

EMPOR d.o.o.
Leskoškova 9a
1000 Ljubljana
T: +386 1 5203820
E: empor@empor.si
www.empor.si

SPAIN

Refrigeration & Climate Control,
S.L.U.
Calle 2A, 7 ; Pol. Ind. Tactica
46980 Paterna (Valencia),
Spain
T: 0034-96-159-49-33
E: direccion@r-cc.es
www.r-cc.es

SWEDEN AND DENMARK

NORDICOLD AB
Datavägen 16,
43632 Askim, Sweden
T: +46 31680440
E: info@nordicold.se
www.nordicold.se



Hidria d. o. o.

Nazorjeva 6a
1000 Ljubljana
Slovenia
T: +386 5 375 60 00
E: sales.fans@hidria.com
www.hidria.com